



CorePro LEDlinear MV

CorePro R7S 118mm 14-100W 830 D

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

Product data

General Information	
Cap-Base	R7S [R7s]
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux	1,600 lumen
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	114.29 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	14 W
Lamp Current (Nom)	74 mA
Wattage Equivalent	100 W

Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	90 ℃
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Shape	Linear
Approval and Application	
Energy Saving Product	Yes
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	14 kWh
EPREL Registration Number	465,216
CE mark	Yes
EU RoHS compliant	Yes

Datasheet, 2023, May 21 data subject to change

CorePro LEDlinear MV

Product Data	
Full product code	871869657879700
Order product name	CorePro R7S 118mm 14-100W 830 D
Order code	929001243702
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10


Material number (12NC)	929001243702	
Full product name	CorePro R7S 118mm 14-100W 830 D	
EAN/UPC - Case	8718696578803	

Dimensional drawing


C

Product	D	С
CorePro R7S 118mm 14-100W 830 D	29 mm	118 mm


Photometric data



Spectral Power Distribution Colour - CorePro R7S 118mm 14-100W 830 D



Colonical Photometries 43 Philips Lighting E.V. Pages 177



Light Distribution Diagram - CorePro R7S 118mm 14-100W 830 D

CorePro LEDlinear MV



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.