



Ledinaire floodlights gen3

BVP164 LED84/840 PSU 70W SWB MDU CE

- - - 840 neutral white - - - Symmetrical

This Ledinaire floodlights range contains a selection of popular off-the-shelf LED luminaires that comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

Product data

General Information		Optical cover/lens type	
Lamp family code	-	Optical cover/lens type	Glass
Light source replaceable	No	Luminaire light beam spread	110° x 110°
Number of gear units	1 unit	Optic type outdoor	Symmetrical wide beam
Driver included	Yes	Operating and Electrical	
Light source engine type	LED	Input Voltage	220 to 240 V
Service tag	No	Line Frequency	50 or 60 Hz
Lighting Technology	LED	Input Frequency	50 or 60 Hz
Embedded control	Movement and light sensor (On/Off)	Initial CLO power consumption	- W
		Average CLO power consumption	70 W
		Power Consumption	70 W
		End CLO power consumption	- W
		Inrush current	3.64 A
		Inrush time	0.0222 ms
		Power Factor (Fraction)	0.9
		Connection	Flying leads/wires
		Cable	Cable 2.0 m without plug
		Number of products on MCB of 16 A type B	31

Ledinaire floodlights gen3

Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Housing Color	Gray
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	203 mm
Overall width	293 mm
Overall height	53 mm
Effective projected area	0.038 m ²
Dimensions (Height x Width x Depth)	53 x 293 x 203 mm
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge Protection (Common/Differential)	2/2 kV
Sustainability rating	-
Protection class IEC	Safety class I
Flammability mark	-
CE mark	Yes
ENEC mark	-
Warranty period	3 years

Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.380, 0.380) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2


Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	80

Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable

Product Data	
Full product code	871951453473599
Order product name	BVP164 LED84/840 PSU 70W SWB MDU CE
Order code	911401884983
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material number (12NC)	911401884983
Full product name	BVP164 LED84/840 PSU 70W SWB MDU CE
EAN/UPC - Case	8719514534834



Dimensional drawing



Ledinaire floodlights gen3

