



MASTERColour CDM-T

MASTERC CDM-T 150W/830 G12 1CT

Range of single-ended, compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Lamps may use electronic or electromagnetic control gear, except 35W/942 and 20W lamps, which must use electronic control gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

Operating and Electrical		Color Designation	
Power Consumption	150.1 W	Color Designation	Warm White (WW)
Voltage (Nom)	96 V	Chromaticity Coordinate X (Nom)	0.434
Voltage (Nom)	96 V	Chromaticity Coordinate Y (Nom)	0.398
General Information		Correlated Color Temperature (Nom)	3000 K
Cap-Base	G12 [G12]	Luminous Efficacy (rated) (Nom)	88 lm/W
Operating Position	UNIVERSAL [Any or Universal (U)]	Color rendering index (CRI)	88
Flux measurement reference	Sphere	Controls and Dimming	
Light Technical		Dimmable	No
Color Code	830 [CCT of 3000K]	Mechanical and Housing	
Luminous Flux	13,000 lumen	Bulb Finish	Clear


MASTERC colour CDM-T

Bulb Shape	T19 [T 19mm]
Approval and Application	
Mercury (Hg) Content (Max)	14.3 mg
Mercury (Hg) Content (Nom)	14.3 mg
Energy Consumption kWh/1000 h	151 kWh
EPREL Registration Number	473,335

Product Data	
Full product code	871150019780115



Order product name	MASTERC CDM-T 150W/830 G12 1CT
Order code	928083705125
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	928083705125
Full product name	MASTERC CDM-T 150W/830 G12 1CT
EAN/UPC - Case	8711500197818

Dimensional drawing



Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERC CDM-T 150W/830 G12 1CT	20 mm	0.75 inch	9 mm	55 mm	57 mm	56 mm	110 mm

Photometric data





Light Distribution Diagram - MASTERC CDM-T 150W/830 G12 1CT

Spectral Power Distribution Colour - MASTERC CDM-T 150W/830 G12 1CT

MASTERCcolour CDM-T

Lifetime



Life Expectancy Diagram - MASTERC CDM-T 150W/830 G12 1CT

Lumen Maintenance Diagram - MASTERC CDM-T 150W/830 G12 1CT

