

Product Data Sheet

GWS4424AA830


SMART [4]




Smart [4] is a series of LED indoor appliances suitable for the lighting of industries and sports facilities. It is available in HE (High Efficiency), HLO (High Lumen Output) and integrated DALI Emergency. Three different sizes available: 1M, 2M and 4M. The body is made of "Halogen-free" nylon loaded with grey glass fibre (RAL7035) with vent and anti-condensation device, heat dissipation device in aluminium alloy EN AB 44300. It is equipped with a dual optical system that includes a metallic reflector with ARRAY optics and a metallic reflector with UV stabilized PMMA lenses, with high efficiency, which allow a wide variety of light distributions 30°, 60°, 90°, Asymmetric and Elliptical. The version with through wiring has pre-wired mechanical and electrical connection components. Suspension, wall and projection appliances can be installed. It is available with three types of Colour Temperature (3000K / 4000K / 5700K), Color Rendering Index CRI>80 and two power supply options (ON/OFF or DALI).

| GENERAL INFORMATION | | OPTIC AND ILLUMINATING FEATURES | |
|-------------------------------------|--|---|--|
| Context | Lighting for industries and large sports facilities | Optic | Array |
| Luminaire | LED Industrial Reflector | Unified Glare Rating | UGR ≤ 25 |
| Application | Internal | Unique digital code (Datamatrix) | Datamatrix |
| Efficacy (lm/W) | 154 | Colour | Grey RAL 7035 |
| Colour temperature | 3000 K | Type of light source | LED |
| Colour Rendering Index | CRI>80 | Standard Deviation Colour Matching | SDCM = 3 |
| LED Lifetime | L90B10 (Tq+25°C) = 100.000 h - L90B10 (Tq+50°C) = 50.000 h | Photobiological Risk Class | RG0 |
| Weight (kg) | 15 | Standard | EN 60598-2-22 ; EN 60598-1 ; EN 60598-2-24 |
| Warranty | 5 years | ELETRICAL AND LIGHTING FEATURES | |
| Stocking temperature | -40 +70 °C | Supply voltage | 220 - 240 V |
| Operating temperature | 0 ÷ +40 °C | Rated frequency (Hz) | 50/60 Hz |
| MATERIALS | | Driver | Included |
| Body | PA6 "Halogen Free" loaded fibreglass | Shield type | Tempered glass Thickness 4mm |
| Overvoltage protection | DM 6 kV / CM 10 kV | Optic | Metallized polycarbonate reflector |
| Control System | 1 x DALI DT6 + 1 x DALI DT1 (Emerg. 3h) | Gasket | anti-aging silicone |
| INSTALLATION AND MAINTENANCE | | Locking Hook | - |
| Mounting and installation | Ceiling light - Suspension | External screw | Stainless steel |
| Tilt | - | Colour | Grey RAL 7035 |
| Wiring | With GW connect watertight connector | STANDARDS AND APPROVALS | |
| Fixing | - | Classification | - |
| Light source replaceability | By professional | Device with reduced surface temperature | Yes |
| Controlgear replaceability | By professional | DIN 18032-3 certification | - |
| Driver Box | Built-in | IPEA | - |
| Maximum surface exposed to the wind | 0,390 m ² | Insulation class | I |
| | | IP degree | IP65 |
| | | Mechanical resistance | IK08 |
| | | Glow Wire Test | 850 °C |

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



Product Data Sheet
GWS4424AA830

SMART [4]

STANDARDS/APPROVALS

