

# PRODUCT DATASHEET

## 64333 C 40-15

Halogen lamps with reflector, current-controlled, 30...40 W | Halogen lamps with reflector, current-controlled, 30...40 W



---

## TECHNICAL DATA

### Electrical data

Nominal wattage	40 W
Construction wattage	40.00 W
Nominal current	6.6 A

### Photometrical data

Luminous intensity	10000 cd
Color temperature	3400 K
Light color	34

### Dimensions & Weight

Overall length	37.00 mm
Length with base excl. base pins/connection	37.00 mm
Diameter	35.3 mm
Product weight	15.00 g

### Lifespan

Lifespan	1500 h
----------	--------

### Additional product data

Base (standard designation)	Leads w/male flat connectors
Mercury content	0.0 mg

### Capabilities

Burning position	h45
------------------	-----

### Country-specific categorizations

Order reference	64333
-----------------	-------

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	Leads w/male flat connectors
Length	35.00 mm
Height	35.3 mm
Width	35.3 mm

---

### Safety advice

- To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

---

**DOWNLOAD DATA****DOWNLOAD DATA**

PRODUCT DATASHEET



Advertisements

---

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321104885	Folding box 1	50 mm x 34 mm x 34 mm	21.33 g	0.06 dm <sup>3</sup>
4008321104892	Shipping box 20	191 mm x 133 mm x 85 mm	448.00 g	2.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**References / Links**

- For more information on airfield lamps see the brochure: "The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.