

# PRODUCT DATASHEET DULUX D 26W-840 G24D-3 10X1 RU OSRAM

OSRAM DULUX® D | CFLni, 2 tubes, with 2-pin base for CCG operation



# Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

### **Product benefits**

- Improved maintenance

### Product features

- Good color rendering index
- Short and compact pin-base lamp with double-turn tubes
- Single-ended two-pin plug-in G24d base



# TECHNICAL DATA

# Electrical data

Nominal wattage	26 W
Construction wattage	26.90 W
Nominal voltage	105 V
Nominal current	0.33 A

# Photometrical data

Luminous flux	1750 lm
Luminous efficacy	67 lm/W
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Rated LLMF at 2,000 h	0.85
Rated LLMF at 4,000 h	0.78
Rated LLMF at 6,000 h	0.76
Rated LLMF at 8,000 h	0.75

# Dimensions & Weight

Overall length	172.00 mm
Diameter	12.00 mm
Product weight	43.00 g

# Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.81

# Additional product data

Base (standard designation)	G24d-3
Mercury content	1.6 mg

# Capabilities

Dimmable	No

# Certificates & Standards

Energy efficiency class	G
Energy consumption	27.00 kWh/1000h

# Country-specific categorizations

|--|

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G24d-3
Correlated colour temperature type	SINGLE_VALUE
Length	172.00 mm
Height	12.00 mm
Width	12.00 mm
EPREL ID	546437
Model number	AC34212

### **EQUIPMENT / ACCESSORIES**

- Suitable for operation on conventional control gear

# Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854123047	Folding box	36 mm x 36 mm x 179 mm	53.00 g	0.23 dm <sup>3</sup>
4099854123054	Shipping box 10	187 mm x 81 mm x 196 mm	605.00 g	2.97 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.