

DURE 3


SLI043021NW_PW

See
more

Downlight luminaire DURE 3, with a power of 5 W, high light efficacy 130 lm/W. It has a high IP54 rating, making it ideal for use in rooms with high humidity. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Designed for recessed mounting.

IP54

IK06



Power	5 W	Voltage	230 V
Luminous flux*	650 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	110 °
IK	6	Degree of protection (IP)	IP54


Technical data

Code	SLI043021NW_PW
Power	5 W
Nominal current	36 mA
Voltage	230 V
Energy consumption	5 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	650 lm (360°)
Luminous flux**	500 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC+PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	95x31 mm
Mounting hole	72 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



Related documents



 User manual




 Declaration of Conformity



 Photometric file



 3D model

