



MASTER TL-D Super 80

MASTER TL-D Super 80 1m 36W/830 SLV/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Lamp Current (Nom)		0.560 A	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Controls and Dimming			
Flux measurement reference	Sphere	Dimmable	Yes		
Light Technical		Mechanical and Housing			
Color Code	830 [CCT of 3000K]	Bulb Shape	T8 [26 mm (T8)]		
Luminous Flux	3,070 lumen	Approval and Application			
Color Designation	Warm White (WW)	Mercury (Hg) Content (Nom)	1.7 mg		
Chromaticity Coordinate X (Nom)	0.44	Energy Consumption kWh/1000 h	37 kWh		
Chromaticity Coordinate Y (Nom)	0.403	EPREL Registration Number	423,417		
Correlated Color Temperature (Nom)	3000 K	Product Data			
Luminous Efficacy (rated) (Nom)	86 lm/W	Full product code	871150055874940		
Color rendering index (CRI)	82	Order product name	MASTER TL-D Super 80 1m 36W/830 SLV/25		
Operating and Electrical		Order code	927923083014		
Power Consumption	36.6 W				

MASTER TL-D Super 80

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material number (12NC)	927923083014
Full product name	MASTER TL-D Super 80 1m 36W/830 SLV/25


EAN/UPC - Case	8711500558756
----------------	---------------

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80 1m 36W/830 SLV/25	28 mm	970.0 mm	977.1 mm	974.7 mm	984.2 mm

Photometric data




Spectral Power Distribution Colour - MASTER TL-D Super 80 1m 36W/830 SLV/25

Lifetime




Life Expectancy Diagram - MASTER TL-D Super 80 1m 36W/830 SLV/25



Life Expectancy Diagram - MASTER TL-D Super 80 1m 36W/830 SLV/25

MASTER TL-D Super 80

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 1m 36W/830
SLV/25

