

VIRGA 2 W0JP10659

LED luminaire VIRGA 2, with a power of 27 W, high light efficacy 125 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 90° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.





| Power | 27 W | Voltage | 230 V |
|--------------------|--------|---------------------------|---------|
| Colour temperature | 4000 K | Colour of light | 940 |
| Beam angle | 90 ° | Degree of protection (IP) | IP54/20 |

www.spectrumled.pl



Technical data

| Code WOJP10659 | C |
|----------------------------------|------|
| Power 27 W | 2 |
| Nominal current 129 mA | |
| Voltage 230 V | |
| rgy consumption 27 kWh/100 | ۱NP |
| Frequency 50HZ Hz | 1011 |
| Protection class II | |
| r supply included + | |
| acturer of power BRIDGELUX | |
| supply | |
| Power factor 0.93 | |
| ul luminous flux* 3375 lm (36 | 50°) |
| Luminous flux** 2700 lm (36 | 50°) |
| Lamp efficacy 125 lm/W | |
| lour temperature 4000 K | |
| Colour of light 940 | |
| Beam angle 90 ° | |
| RA 90 | |
| t source included Yes | |
| cer of LED diodes CREE | |
| color SDCM max 3 | |
| mperature range -20/+40 ° | |
| Lifespan 50000 h | |
| Housing material Aluminum | |
| of protection (IP) IP54/20 | |
| Colour White | |
| imension (AxBxC) 230x74 mm | ı |
| Mounting hole 0210 mm | |
| For use Inside | |
| ssembly method Recessed | |
| Application Inside | |
| Made in PL | |
| | |

Related documents



Declaration of Conformity



