MQ603 Downlight 24W 1800lm 3000K 100° G2



PRODUCT INFORMATION

Product code 60500 IE-DL-MQ603-24-2000-3000K-1 Product code (long) Product description MQ603 Downlight 24W 1800lm 5999097605005 EAN code Category Downlight

PHOTOMETRIC DATA

Nominal luminous flux 2000 Lm Rated luminous flux 2000 Lm Nominal beam angle (half-peak value) 100° 100° Rated beam angle (half-peak value) Correlated colour temperature 3000K Colour temperature designation Warm white 80 Ra Colour rendering index (Ra) 7 SDCM Colour consistency Warm-up time to reach 60% of full light 1 s

ELECTRICAL DATA

24 W Nominal wattage 24,0 W Rated wattage 220-240V Nominal voltage 50/60Hz Operating frequency Nominal current 120 mA Power factor 0.95 Wattage of equivalent filament lamp 180W

240 mm Overal diameter Overall height 53mm Lamp shape Round Weight 0,610 kg

LIFE SPAN

Nominal life time 35000 h Rated life time 35000 h Number of switching cycles 15000 Warranty 3 years

ADDITIONAL TECHNICAL INFORMATION

Starting time 0,5 s Optimum operating ambient temperature 25°C Milky cover Lamp finish Dimming non-dimmable Energy efficiency class 24,0 kWh/100h Energy consumption

IP20 IP rating



