

PRODUCT DATASHEET

HQL 250 W E40

HQL® | Mercury vapor lamps for open and enclosed luminaires



Areas of application

- Factories and workshops
- Industrial installations
- Streets
- Car parks, courtyards
- Pedestrian zones, public squares
- Parks and gardens
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires




TECHNICAL DATA

Electrical data

Nominal wattage	250 W
Construction wattage	250.00 W
Nominal voltage	135 V
Ignition voltage	0.198 kVp
Operating mode	Conventional control gear (CCG) without ignitor
Nominal current	2.13 A
PFC capacitor at 50 Hz	18 µF

Photometrical data

Luminous flux	13000 lm
Luminous efficacy	52 lm/W
Color temperature	3900 K
Color rendering index Ra	41
Light color	439
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.92
Rated LLMF at 6,000 h	0.91
Rated LLMF at 8,000 h	0.89
Rated LLMF at 12,000 h	0.86
Rated LLMF at 16,000 h	0.85
Rated LLMF at 20,000 h	0.75
Rated lamp efficacy (standard co.)	52 lm/W
UV protection	No



Dimensions & Weight

Overall length	226.00 mm
Diameter	91 mm
Product weight	160.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	350 °C
Maximum permitted base edge temperature	250 °C

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.97
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.90
Rated lamp survival factor at 12,000 h	0.75
Rated lamp survival factor at 16,000	0.68
Rated lamp survival factor at 20,000 h	0.60
Lifespan B10	8000 h
Lifespan B5	6000 h
Lifespan B50	24000 h
Operation mode LLMF/LSF	50 Hz

Additional product data

Base (standard designation)	E40
Mercury content	39.1 mg
Mercury-free	No
Design / version	Coated
Product remark	As of April 2015 not compliant with ErP directive 245/2009

Capabilities

Dimmable	No
Burning position	Any
Enclosed luminaire required	No

Certificates & Standards

Energy efficiency class	B
Energy consumption	275.00 kWh/1000h

Country-specific categorizations

ILCOS	QE/R-250-H/E/S-E40-91/226
Order reference	HQL 250W E40

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E40
Length	226.00 mm
Height	91 mm
Width	91 mm

DOWNLOAD DATA

Documents and certificates



User instruction

Photometric and lighting design files



Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300015064	Round wrap 1	230 mm x 93 mm x 97 mm	224.00 g	2.07 dm ³
4008321865021	Shipping box 12	390 mm x 267 mm x 292 mm	2980.00 g	30.41 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.