



CorePro LEDspot MV



Corepro LEDspot 4.6-50W GU10 840 36D

CorePro LEDspots are a perfect fit for spot lighting and deliver warm halogen-like light. These GU10 LED spot lights are compatible with most existing fixtures with a GU10 LED base and are designed as a retrofit replacement for halogen or incandescent spots. CorePro LEDspots deliver significant energy savings and minimize maintenance costs.

Product data

General Information	
Cap-Base	GU10
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Narrow Cone
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	36 degree(s)
Luminous Flux	390 lm
Luminous Intensity (Nom)	770 cd
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	84.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	390 lm
Photobiological safety according to EN 62471	RG1

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	4.6 W
Lamp Current (Nom)	39 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.5
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	72 °C
Controls and Dimming	
Dimmable	No
	<u> </u>
Mechanical and Housing	
Bulb Shape	PAR16
Net Weight (Piece)	0.045 kg


Datasheet, 2025, March 17 data subject to change

CorePro LEDspot MV

Approval and Application	
Energy Efficiency Class	F
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	5 kWh
EPREL Registration Number	391859
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.4
Application Conditions	
can it be used in closed luminaires	No


Product Data	
Order product name	Corepro LEDspot 4.6-50W GU10 840
	36D
Full product name	Corepro LEDspot 4.6-50W GU10 840
	36D
Full product code	871869672839000
Order code	929001218202
Material Nr. (12NC)	929001218202
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696728390
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696728406

Dimensional drawing




Product	D	С
Corepro LEDspot 4.6-50W GU10 840 36D	50 mm	54 mm

Photometric data






Accent Lighting Spots - Corepro LEDspot 4.6-50W GU10 840 36D



Light Distribution Diagram - Corepro LEDspot 4.6-50W GU10 840 36D


CorePro LEDspot MV


Photometric data



Spectral Power Distribution Colour - Corepro LEDspot 4.6-50W GU10 840 36D

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - Corepro LEDspot 4.6-50W GU10 840 36D



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.