

PRODUCT DATASHEET

HE SL 28 W/865

SMARTLUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency




TECHNICAL DATA

Electrical data

| | |
|-------------------------------------|---------|
| Nominal wattage | 28 W |
| Construction wattage | 27.90 W |
| Nominal voltage | 220 V |
| Rated lamp efficacy (HF data 25 °C) | 86 |

Photometrical data

| | |
|-------------------------------------|---------|
| Luminous flux | 2400 lm |
| Luminous efficacy | 85 lm/W |
| Luminous flux at 25 °C | 2400 lm |
| Luminous flux at 35 °C | 2750 lm |
| Color temperature | 6500 K |
| Color rendering index Ra | ≥80 |
| Light color | 865 |
| Rated LLMF at 2,000 h | 0.95 |
| Rated LLMF at 4,000 h | 0.92 |
| Rated LLMF at 6,000 h | 0.91 |
| Rated LLMF at 8,000 h | 0.90 |
| Rated LLMF at 12,000 h | 0.90 |
| Rated LLMF at 16,000 h | 0.90 |
| Rated LLMF at 20,000 h | 0.89 |
| Rated lamp efficacy (HF data 25 °C) | 86 |



Dimensions & Weight

| | |
|---|------------|
| Overall length | 1149.00 mm |
| Length with base excl. base pins/connection | 1149 mm |

| | |
|------------------|---------|
| Diameter | 16,0 mm |
| Tube diameter | 16 mm |
| Maximum diameter | 16 mm |
| Product weight | 90.00 g |

Temperatures & operating conditions

| | |
|-----------------------------------|---------|
| Rated ambient temp.w.max.luminous | 35.0 °C |
|-----------------------------------|---------|

Lifespan

| | |
|--|------|
| Rated lamp survival factor at 2,000 h | 0.99 |
| Rated lamp survival factor at 4,000 h | 0.99 |
| Rated lamp survival factor at 6,000 h | 0.99 |
| Rated lamp survival factor at 8,000 h | 0.99 |
| Rated lamp survival factor at 12,000 h | 0.99 |
| Rated lamp survival factor at 16,000 | 0.90 |
| Rated lamp survival factor at 20,000 h | 0.50 |
| Operation mode LLMF/LSF | HF |

Additional product data

| | |
|-----------------------------|--------|
| Base (standard designation) | G5 |
| Mercury content | 1.2 mg |

Capabilities

| | |
|---------------------|-----|
| Suitable for indoor | Yes |
|---------------------|-----|

Certificates & Standards

| | |
|-------------------------|-----------------|
| Energy efficiency class | A+ |
| Energy consumption | 30.69 kWh/1000h |

Country-specific categorizations

| | |
|-----------------|---------------|
| Order reference | HE 28W/865 SL |
|-----------------|---------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|---|------------|
| Light source cap-type (or other electric interface) | G5 |
| Length | 1149.00 mm |
| Height | 16,0 mm |
| Width | 16,0 mm |

DOWNLOAD DATA

Photometric and lighting design files



Spectral power distribution

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4008321335623 | Sleeve 1 | 1,164 mm x 18 mm x 18 mm | 109.00 g | 0.38 dm ³ |
| 4052899046856 | Shipping box 20 | 1,191 mm x 104 mm x 88 mm | 3018.00 g | 10.90 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.