



CorePro LEDcapsule LV



CorePro LEDcapsuleLV 1.7-20W G4micro 827

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.

Product data

General Information	
Cap-Base	G4
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux	200 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	117 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG0
Operating and Electrical	
Input Frequency	- Hz

Power Consumption	1.7 W
Lamp Current (Nom)	235 mA
Wattage Equivalent	20 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.5
Voltage (Nom)	ac electronic 12 V
Temperature	
T-Case Maximum (Nom)	60 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Clear Plastic
Bulb Shape	Capsule
Net Weight (Piece)	0.002 kg

Datasheet, 2025, March 17 data subject to change

CorePro LEDcapsule LV


Approval and Application	
Energy Efficiency Class	F
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	2 kWh
EPREL Registration Number	1879160
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C
Application Conditions	

No

Product Data	
Order product name	CorePro LEDcapsuleLV 1.7-20W
	G4micro 827
Full product name	CorePro LEDcapsuleLV 1.7-20W
	G4micro 827
Full product code	872016930047700
Order code	929003779002
Material Nr. (12NC)	929003779002
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169300477
Numerator - Packs per outer box	12
EAN/UPC - Case	8720169300484


Dimensional drawing


can it be used in closed luminaires




Product	D	С
CorePro LEDcapsuleLV 1.7-20W G4micro 827	9.5 mm	37.5 mm

Photometric data








General uniform lighting - CorePro LEDcapsuleLV 1.7-20W G4micro 827


CorePro LEDcapsule LV


Photometric data



Spectral Power Distribution Colour - CorePro LEDcapsuleLV 1.7-20W G4micro 827

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro LEDcapsuleLV 1.7-20W G4micro 827



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.