


# Eclipse MultiLED CCT



- LED wall/ceiling luminaire with adjustable power and light output option suitable for education and commercial applications and ancillary areas
- One product with integral driver dip-switch
- Internal CCT selector switch allows the installer to choose the CCT between 3000K, 4000K and 6500K
- Corridor function options available for effective reduction in energy consumption
- Spun aluminium base with dished opal Visiluxe diffuser
- BESA box fixing versatile mounting options
- Option of white, chrome or satin chrome housing



**OCTO**  
Option Available

Powered by  
**CASAMBI**

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
230V	50/60Hz	-10°C to 25°C	L70 54,000	Ra 80	6	110°	1	IP20	IK08

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	TRADE
<b>AECLED/W/CCT</b>	CCT Selectable - White			1193lm (4000K - 11W)	108lm (4000K - 11W)	<b>£157.00</b>
<b>AECLED/CH/CCT</b>	CCT Selectable - Chrome	11W/14W/25W	3000K/4000K/6500K	1493lm (4000K - 14W)	107lm (4000K - 14W)	<b>£174.00</b>
<b>AECLED/SC/CCT</b>	CCT Selectable - Satin Chrome			2846lm (4000K - 25W)	114lm (4000K - 25W)	<b>£174.00</b>

CODE (OPTIONS)	DESCRIPTION	TRADE	CODE (OPTIONS)	DESCRIPTION	TRADE
<b>/M3</b>	Self-Test Emergency	<b>+ £90.00</b>	<b>/DD</b>	Digital Dimming (DD1/DD3/DD4)	<b>+ £95.00</b>
<b>/DM3</b>	DALI Emergency	<b>+ £205.00</b>	<b>/MWS</b>	Integral Microwave Sensor	<b>+ £60.00</b>
<b>/OCTO</b>	OCTO Smart Control	<b>+ £155.00</b>	<b>/CF</b>	Corridor Function	<b>+ £37.00</b>