

# PRODUCT DATASHEET

## 64386

Halogen lamps, current-controlled, single-ended | Halogen lamps, current-controlled, single-ended



---

## TECHNICAL DATA

### Electrical data

Nominal wattage	200 W
Construction wattage	200.00 W
Nominal current	6.6 A

### Photometrical data

Luminous flux	4700 lm
Luminous efficacy	23 lm/W
Color temperature	3200 K
Color rendering index Ra	100
Light color	1032

### Dimensions & Weight

Overall length	47.00 mm
Light center length (LCL)	33,0 mm
Diameter	13,5 mm
Product weight	3.3 g

### Lifespan

Lifespan	1500 h
----------	--------

### Additional product data

Base (standard designation)	G6.35
Mercury content	0.0 mg

### Capabilities

Burning position	s90
------------------	-----

### Country-specific categorizations

Order reference	64386 200W G6.3
-----------------	-----------------

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G6.35
Length	47.00 mm
Height	13,5 mm
Width	13,5 mm



---

### Safety advice

– To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms

(protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

**DOWNLOAD DATA**

DOWNLOAD DATA	
	PRODUCT DATASHEET
	Advertisements

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321106407	Folding box 1	70 mm x 23 mm x 28 mm	7.00 g	0.05 dm <sup>3</sup>
4008321106414	Shipping box 40	144 mm x 107 mm x 121 mm	280.00 g	1.86 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**References / Links**

- For more information on airfield lamps see the brochure: "The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.