

# SLI035056WW\_PW\_IP44

SLI035056WW\_PW\_IP44



---

Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5200 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>120 °</b>
Degree of protection (IP)	<b>IP44/IP20***</b>		

---

## Technical data


---

Code	SLI035056WW_PW_IP44
Power	40 W
Nominal current	186 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	PHILIPS
Power factor	0.9
Useful luminous flux*	5200 lm (360°)
Luminous flux**	4500 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP44/IP20***
Colour	White
Dimension (AxBxC)	595x595x26 mm
Mounting hole	575x575mm mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PL

## Related documents

---



 Declaration of Conformity

---