

# NOCTIS LUX 2

SLI029039WW\_CZUJNIK



See  
more

Floodlight NOCTIS LUX 2, with a power of 30 W. It has a high IP44 rating, making it ideal for use in areas of high humidity. It shines with a warm light (3000K). Designed for surface mounting.

IP44



Power	<b>30 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2740 lm (120°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>100 °</b>
Degree of protection (IP)	<b>IP44</b>		

## Technical data


---

Code	SLI029039WW_CZUJNIK
Power	30 W
Nominal current	130 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2740 lm (120°)
Luminous flux**	2600/2740 lm (360°)
Lamp efficacy	87 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC, GLASS
Degree of protection (IP)	IP44
Colour	Black
Dimension (AxBxC)	188x160x28 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC

## Related documents

---



 Declaration of Conformity



 Photometric file