



CoreLine Trunking Gen2

LL217X 80S/840 1x PSU WB 5x1.5

LL217X | Coreline Trunking Gen2 - 80S | LED Module, system flux 8000 lm - Power supply unit (ON/OFF) - Wide beam - 84° x 84°

CoreLine Trunking Gen2 is a light-line system that is designed for simplicity. It comes in a choice of lengths, flux packages and beam shapes to suit every project and application. Easy to use and integrate with spots and sensors, CoreLine Trunking Gen2 provides consistent, high-quality lighting with added protection against accidental water ingress. The innovative system is also easy to assemble and install for faster retrofits and refurbishments.

Product data

General Information	
Lamp family code	80S [LED Module, system flux 8000 lm]
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Service tag	Yes
Product family code	LL217X [Coreline Trunking Gen2]
Lighting Technology	LED
Value ladder	Value

Light Technical	
Luminous Flux	8,000 lumen
Correlated Color Temperature (Nom)	4000 K

Luminous Efficacy (rated) (Nom)	157 lm/W
Color rendering index (CRI)	>80
Beam angle of light source	120 degree(s)
Light source color	840 neutral white
Optic type	Wide beam
Luminaire light beam spread	84° x 84°
Unified glare rating CEN	22

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Initial CLO power consumption	- W

CoreLine Trunking Gen2

Average CLO power consumption	- W
Power Consumption	51 W
Inrush current	19 A
Inrush time	0.280 ms
Power Factor (Fraction)	0.95
Connection	Connection unit 5-pole
Cable	-
Number of products on MCB of 16 A type B	24

Temperature

Ambient temperature range	-20 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Steel
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Housing Color	White RAL9016
Optical cover/lens finish	Frosted
Overall length	1,700 mm
Overall width	80 mm
Overall height	50 mm
Dimensions (Height x Width x Depth)	50 x 80 x 1700 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	-

CE mark	Yes
ENEC mark	ENEC plus mark
Warranty period	5 years
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38, 0.38) SDCM <3
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Control gear failure rate at median useful life 100000 h	0.1 %
Lumen maintenance at median useful life* 50000 h	L85
Lumen maintenance at median useful life* 100000 h	L75

Application Conditions


Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes

Product Data

Full product code	871951410794600
Order product name	LL217X 80S/840 1x PSU WB 5x1.5
Order code	910925867537
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material number (12NC)	910925867537
Full product name	LL217X 80S/840 1x PSU WB 5x1.5
EAN/UPC - Case	8719514107946



Dimensional drawing



CoreLine Trunking Gen2

