



MASTER - LED HID HPI

TForce LED HPI UN 95W E40 840 WB

Philips LED Highbay lamps give you a quick and easy payback solution to replace HID alternatives in high-bay applications. TrueForce LED solutions give you the LED benefits of energy-efficiency and a long lifetime for a low initial investment. The design of TrueForce LED enables the direct retrofit of HID lamps with TrueForce LED lamps without changing the fixtures or gear. In fact, the TrueForce LED lamp is compatible with both 250W and 400W gears to maximize the feasibility of such retrofits. Ignitor smart logic eliminates ignitor failure and continued ignition, which may generate overheating and EMI risks. Multiple beam angle options and a high color rendering index enhance the lighting distribution in medium and high-bay applications, while creating a comfortable, safe and highly-productive environment.

Warnings and Safety

- Installation should always be performed by a qualified electrician or installer. Use the installation guide for instructions.

Product data

General Information		Operating and Electrical	
Cap-Base	E40 [E40]	Correlated Color Temperature (Nom)	4000 K
Nominal lifetime	50,000 hour(s)	Luminous Efficacy (rated) (Nom)	136 lm/W
Switching Cycle	50,000	Color Consistency	<6
Lighting Technology	LED	Color rendering index (CRI)	80
Flux measurement reference	Wide Cone	LLMF At End Of Nominal Lifetime (Nom)	70 %
Light Technical		Line Frequency	50 Hz
Color Code	840 [CCT of 4000K]	Input Frequency	50 Hz
Beam Angle (Nom)	120 degree(s)	Power Consumption	95 W
Luminous Flux	13,000 lumen	Lamp Current (Nom)	500 mA
Color Designation	Cool White (CW)	Wattage Equivalent	250 W

MASTER - LED HID HPI

Starting Time (Nom)	0.5 s
Warm-up time to 60% light	1 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V

Temperature

Ambient temperature range	-20 °C to 45 °C
T-Case Maximum (Nom)	55 °C

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Shape	Others
------------	--------

Approval and Application


Energy Consumption kWh/1000 h	95 kWh
-------------------------------	--------

EPREL Registration Number	403,625
CE mark	Yes
EU RoHS compliant	Yes

Product Data



Full product code	871869975369600
Order product name	TForce LED HPI UN 95W E40 840 WB
Order code	929002350802
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3
Material number (12NC)	929002350802
Full product name	TForce LED HPI UN 95W E40 840 WB
EAN/UPC - Case	8718699753702

Dimensional drawing



Product	D	C
TForce LED HPI UN 95W E40 840 WB	250 mm	290 mm

Photometric data




© 2023 Philips Lighting B.V. Page 11

Spectral Power Distribution Colour - TForce LED HPI UN 95W E40 840 WB

MASTER - LED HID HPI

Photometric data



Light Distribution Diagram - TForce LED HPI UN 95W E40 840 WB

Lifetime



Life Expectancy Diagram - TForce LED HPI UN 95W E40 840 WB



Lumen Maintenance Diagram - TForce LED HPI UN 95W E40 840 WB

