

ENCANTA

SLI003034CCT_PW



See
more

LED luminaire ENCANTA with the possibility of changing the light color (CCT), with a power of 6 W, high light efficacy 142 lm/W. Thanks to the ability to change the color temperature (CCT) in the range from 3000K to 6000K, we can adjust the light color depending on our needs and preferences. It has a high IP54 rating, making it ideal for use in rooms with high humidity. The CCT function allows you to changes to the colour temperature of light (3000/4000/6000K). Designed for recessed mounting.

CCT**IP54**

| | | | |
|---------------------------|----------------------|--------------------|-------------------------|
| Power | 6 W | Voltage | 230 V |
| Luminous flux* | 850 lm (360°) | Colour temperature | 3000/4000/6000 K |
| Colour of light | CCT | Beam angle | 120 ° |
| Degree of protection (IP) | IP54 | | |

Technical data


| | |
|---------------------------|--|
| Code | SLI003034CCT_PW |
| Power | 6 W |
| Nominal current | 50 mA |
| Voltage | 230 V |
| Energy consumption | 6 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power factor | 0,5 |
| Useful luminous flux* | 850 lm (360°) |
| Luminous flux** | 300 lm (360°) |
| Lamp efficacy | 142 lm/W |
| Colour temperature | 3000/4000/6000 K |
| Colour of light | CCT |
| Beam angle | 120 ° |
| RA | 80 |
| Light source included | + |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | PLASTIC |
| Degree of protection (IP) | IP54 |
| Colour | Black |
| Dimension (AxBxC) | 230x84x60 mm |
| Mounting hole | 226x85x52 mm |
| For use | Inside/Outside |
| Assembly method | Recessed |
| Application | INT/EXT |
| Made in | PRC |
| Other | Light color change function 3000K/4000K/6000K , |

Related documents



 User manual



 Declaration of Conformity



 Photometric file

