



CorePro - LED HID SON-T



TForce Core LED road 40W 727 E40 MV

The Philips CorePro LED HID SON-T lamps offer you an easy, short-payback LED solution to replace High Intensity Discharge (HID) lamps. This new generation of products brings all the energy-efficiency and long-lifetime benefits of LED to HID replacement, while providing instant saving with a low initial investment.

Furthermore, they're designed to have the same lamp size and light distribution as other HID lamps, so you will never know the difference. All thanks to our HighPower LED filament technology. Plus, its unique IP65 design means it can be used for outdoor applications

Warnings and Safety

• Please refer to the installation guide or consult a Philips Lighting representative for the wiring diagram and instructions.

Product data

General Information	
Cap-Base	E40
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere

Light Technical	
Color Code	727 [CCT of 2700K]
Beam Angle (Nom)	330 degree(s)
Luminous Flux	6,500 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	162 lm/W

Color Consistency	<6
Color rendering index (CRI)	70
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG1

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power Consumption	40 W
Lamp Current (Nom)	178 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
Ballast Compatibility	Mains

CorePro - LED HID SON-T

Inrush current at mains	29
Max. lamp no. on MCB B type 10A - Mains	6
Max. lamp no. on MCB B type 10A – EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 10A – EM ballast with Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A - Mains	9
Max. lamp no. on MCB B type 16A – EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A – EM ballast with Compensation Capacitor.	-

Temperature

T-Case Maximum (Nom)	48.7 °C
----------------------	---------

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	T46
Net Weight (Piece)	0.155 kg

Approval and Application

Energy Efficiency Class	C
Energy Consumption kWh/1000 h	40 kWh

EPREL Registration Number	1617389
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	2
Ambient temperature range	-30 to +45 °C


Application Conditions

can it be used in closed luminaires	Yes
-------------------------------------	-----

Product Data

Order product name	TForce Core LED road 40W 727 E40 MV
Full product name	TForce Core LED road 40W 727 E40 MV
Full product code	872016926775600
Order code	929003731002
Material Nr. (12NC)	929003731002
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169267756
Numerator - Packs per outer box	6
EAN/UPC - Case	8720169267763



Dimensional drawing



Product	D	C
TForce Core LED road 40W 727 E40 MV	47 mm	229 mm


CorePro - LED HID SON-T

Photometric data




Light Distribution Diagram - TForce Core LED road 40W 727 E40 MV

General uniform lighting - TForce Core LED road 40W 727 E40 MV




Spectral Power Distribution Colour - TForce Core LED road 40W 727 E40 MV

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - TForce Core LED road 40W 727 E40 MV

