



AspiraVision Compact for CDM

HID-AV C 35-70 /S CDM 220-240V 50/60Hz

AspiraVision is the mark of excellence in HID electronic gear technology – high-end, compact, lightweight and easy to use, with added features for optimal performance of 35, 50 and 70 W CDM lamps. The recently added switching function provides maximum flexibility for users by integrating three different wattage choices into a single driver.

Product data

General Information		T-Case Lifetime (Nom)		80 °C	
Number of Lamps	1 piece/unit	Controls and Dimming			
Operating and Electrical		Control Interface			--
Input Voltage	220 to 240 V	Mechanical and Housing			
Line Frequency	50 to 60 Hz	Housing			/S
Input Frequency	50 to 60 Hz	Approval and Application			
Earth Leakage Current (Max)	0.25 mA	Surge Protection (Common/Differential)			EN61547 (L-L 2kV, L-G 4kV) kV
Inrush Current Width	10 ms	Safety Standard			EN 61347-2-12 and 2-1
Inrush Current Peak (Max)	8 A	Environmental Standard			ISO 14001
Number of Products on MCB (16A Type B) (Nom)	58	Approval Marks			F-Marking CE marking ENEC certificate VDE certificate CB Certificate VDE-EMC marking
Wiring		Product Data			
Cable Length From Device to Lamp	2 m	Full product code			871829123310700
Connector Type	WAGO series 804	Order product name			HID-AV C 35-70 /S CDM 220-240V 50/60Hz
Temperature		Order code			913700683866
Ambient temperature range	-20 °C to 55 °C	Numerator - Quantity Per Pack			1

AspiraVision Compact for CDM

Numerator - Packs per outer box	12
Material number (12NC)	913700683866
Full product name	HID-AV C 35-70 /S CDM 220-240V 50/60Hz

EAN/UPC - Case	8718291233114
----------------	---------------

Dimensional drawing

— A2

Product	D1	C1	A1	A2	B1	B2
HID-AV C 35-70 /S CDM 220-240V 50/60Hz	4.5 mm	32.1 mm	110.0 mm	98.5 mm	75.0 mm	63.5 mm

