


Volo CCT Recessed Modular



- Architectural LED recessed modular suitable for education, commercial and healthcare applications
- High performance indirect recessed luminaire
- Can be surface and suspended, suspension kit supplied separately
- Dual direct/indirect output. Direct from the centre micro-prism central diffuser coupled with indirect output from the side diffuser sections. Providing a perfect combination for task and ambient lighting from one source
- Selectable CCT between 3000K and 4000K
- OCTO tunable white option (3000K–6500K)
- Integral PIR option discreetly positioned in the end cap
- High performance optics provide high efficiency while still offering optimum glare control and comfort for task/office applications
- TP(a) as standard



AVOLO
only



AVOLO/TW/OCTO
only



OCTO
Option
Available

Powered by
CASAMBI



PIR Module

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220/240V	50/60Hz	-20°C to 50°C	L80 54,000	Ra 80	3	85°	1	IP40

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR	TRADE
AVOLO	600 x 600 - CCT Selectable	21/34W	3000K/4000K	2700/4200lm (4000K)	128/124lm (4000K)	17	£198.00
AVOLO/TW/OCTO	600 x 600 - Tunable White	42W	2700K-6500K	3210lm (2700K) - 3700lm (6500K)	76lm (2700K) - 88lm (6500K)	17	£393.00

* UGR Value based on (4H - 8H)

CODE (OPTIONS)	DESCRIPTION	TRADE	CODE (OPTIONS)	DESCRIPTION	TRADE
/M3	Emergency	+ £90.00	/PIR	PIR	+ £250.00
/SM3	Self-Test Emergency	+ £121.00	/DD	Digital Dimming (DD1/DD3/DD4)	+ £95.00
/DM3	DALI Emergency	+ £205.00	/OCTO	OCTO Smart Control	+ £195.00

CODE (ACCESSORIES)	DESCRIPTION	TRADE
AVOLO/SK	Suspension Kit 1.5m	£28.00