



CorePro GLASS LED candles and lusters

CorePro LEDCandle ND6.5-60W B35E14827CLG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information	
Cap-Base	E14 [E14]
CE mark	Yes
EU RoHS compliant	Yes
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux	806 lumen
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	124.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80

LLMF At End Of Nominal Lifetime (Nom) 70 %	
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	6.5 W
Lamp Current (Nom)	50 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.55
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	55 °C

CorePro GLASS LED candles and lusters

Controls and Dimming

Dimmable No

Mechanical and Housing

Bulb Finish Clear

Bulb Shape B35 [B 35mm]

Approval and Application

Energy Consumption kWh/1000 h 7 kWh

EPREL Registration Number 387,441

Product Data

Full product code 871951434746500

Order product name CorePro LEDCandle ND6.5-60W
B35E14827CLG

Order code 929002028092

Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 10


Material number (12NC) 929002028092

Net weight 0.012 kg

Full product name CorePro LEDCandle ND6.5-60W
B35E14827CLG



EAN/UPC - Case 8719514347472

Dimensional drawing



Product	D	C
CorePro LEDCandle ND6.5-60W B35E14827CLG	35 mm	97 mm

Photometric data




Light Distribution Diagram - CorePro LEDCandle ND6.5-60W B35E14827CLG


Spectral Power Distribution Colour

CorePro GLASS LED candles and lusters


Photometric data



Lifetime



Lumen Maintenance Diagram - CorePro LEDCandle ND6.5-60W B35E14827CLG



Life Expectancy Diagram - CorePro LEDCandle ND6.5-60W B35E14827CLG

