



CorePro LEDlinear MV

CorePro LEDlinear ND 7.5-60W R7S 78mm840

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

Product data

General Information	
Cap-Base	R7S [R7s]
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux	1,000 lumen
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	133.33 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	7.5 W
Lamp Current (Nom)	70 mA
Wattage Equivalent	60 W
	· · · · · · · · · · · · · · · · · · ·

Starting Time (Nom)	0.5 s		
Warm-up time to 60% light	0.5 s		
Power Factor (Fraction)	0.5		
Voltage (Nom)	220-240 V		
Temperature			
T-Case Maximum (Nom)	104 °C		
Controls and Dimming			
Dimmable	No		
Mechanical and Housing			
Bulb Shape	Others		
Approval and Application			
Energy Consumption kWh/1000 h	8 kWh		
EPREL Registration Number	465,220		
CE mark	Yes		
EU RoHS compliant	Yes		
Product Data			
Full product code	871869671396900		
Order product name	CorePro LEDlinear ND 7.5-60W R7S 78mm840		


Datasheet, 2023, May 19 data subject to change

CorePro LEDlinear MV

Order code	929001339102
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material number (12NC)	929001339102


Full product name	CorePro LEDlinear ND 7.5-60W R7S 78mm840
EAN/UPC - Case	8718696713976

Dimensional drawing




Product	D	С
CorePro LEDlinear ND 7.5-60W R7S 78mm840	29 mm	78 mm


Photometric data








Spectral Power Distribution Colour - CorePro LEDlinear ND 7.5-60W R7S 78mm840




Light Distribution Diagram - CorePro LEDlinear ND 7.5-60W R7S 78mm840

CorePro LEDlinear MV

Lifetime





Life Expectancy Diagram - CorePro LEDlinear ND 7.5-60W R7S 78mm840

Lumen Maintenance Diagram - CorePro LEDlinear ND 7.5-60W R7S 78mm840

