

# HALLS LINE 2

SLI048006NW\_PW



See  
more

High bay luminaire HALLS LINE 2, with a power of 75 W, high light efficacy 155 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP66, providing protection against the ingress of dust and water jets. IK10 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for suspended mounting.



Power	<b>75 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>11625 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>60x90 °</b>
IK	<b>10</b>	Degree of protection (IP)	<b>IP66</b>

## Technical data


---

Code	SLI048006NW_PW
Power	75 W
Nominal current	345 mA
Voltage	230 V
Energy consumption	75 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	11625 lm (360°)
Luminous flux**	11250 lm (360°)
Lamp efficacy	155 lm/W
Luminous intensity	11700 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	60x90 °
RA	80
Light source included	Yes
Dimmable	Yes
Working temperature range	-20 +40 °
Lifespan	50000 h
Housing material	Aluminum
IK	10
Degree of protection (IP)	IP66
Colour	Black
Dimension (AxBxC)	547x150x130 mm
For use	Outside/Inside
Assembly method	Suspended
Whether it should work in conditions other than normal	Yes
Made in	PRC


## Related documents

---



 User manual



 Declaration of Conformity



 Photometric file

