Product Data Sheet GWA1242


Connected SMART HOME



Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

2	No. of channels	100 ÷ 240 V ac - 50/60 Hz	Power supply
Zigbee (IEEE 802.15.4)	Radio connections	2	No. modules
-5 ÷ +45 °C	Working temperature	-	Standard
10 dBm	Power output Zigbee	n-condensative) Max 93%	Relative humidity (non
Max. 1,5	Terminal tightening capacity stranded cables (mm ²)	With screw	Wiring terminals
2-channel push-button control panel	Category	pacity Max. 1,5	Terminal tightening ca solid cables (mm ²)
Mains supply voltage	Input voltage	2 (for local command replication or sending additional Zigbee commands)	No. input channels
Blue	LED colour	IP20 (with button key)	IP degree
Yes	Power supply of EGO SMART plate	Via 2 front push buttons (to complete with button key)	Local control

Zigbee control extension if Wissta (22 Zigbee EGAD Style Rottiplatted (Sith Filo fut putish buttons)



TECHNICAL SYMBOLOGY



IP20 (with button key)

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com sat@gewiss.com Last update 20/04/2023 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice

DIMENSIONAL

