

# WOJP11407

WOJP11407



|                           |                       |                    |               |
|---------------------------|-----------------------|--------------------|---------------|
| Power                     | <b>10 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux*            | <b>1500 lm (360°)</b> | Colour temperature | <b>4000 K</b> |
| Colour of light           | <b>Neutral white</b>  | Beam angle         | <b>50 °</b>   |
| Degree of protection (IP) | <b>IP20</b>           |                    |               |

## Technical data

---

|                              |                |
|------------------------------|----------------|
| Code                         | WQJP11407      |
| Power                        | 10 W           |
| Nominal current              | 90 mA          |
| Voltage                      | 230 V          |
| Energy efficiency class      | D              |
| Energy consumption           | 10 kWh/1000h   |
| Frequency                    | 50HZ Hz        |
| Protection class             | II             |
| Power supply included        | +              |
| Manufacturer of power supply | TCI            |
| Power factor                 | 0.93           |
| Useful luminous flux*        | 1500 lm (360°) |
| Luminous flux**              | 900 lm (360°)  |
| Lamp efficacy                | 150 lm/W       |
| Colour temperature           | 4000 K         |
| Colour of light              | Neutral white  |
| Beam angle                   | 50 °           |
| RA                           | 80             |
| Light source included        | +              |
| Producer of LED diodes       | CREE           |
| Uniformity of color SDCM max | 3              |
| Dimmable                     | OPC            |
| Working temperature range    | -20/+40 °      |
| Lifespan                     | 50000 h        |
| Housing material             | Aluminum       |
| Degree of protection (IP)    | IP20           |
| Colour                       | White          |
| Dimension (AxBxC)            | 187x150 mm     |
| Mounting hole                | Ø175 mm        |
| For use                      | Inside         |
| Assembly method              | Recessed       |
| Application                  | Inside         |
| Made in                      | PL             |

## Related documents

---



 Declaration of Conformity

