

PRODUCT DATASHEET

LS V -2000/827/5

LED STRIP V 2000 | LED strips with 2000 lm/m for general applications



Areas of application

- General indoor illumination
- Decorative illumination
- Private living areas

Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy installation, no tools required for connection
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides

Product features

- Flexible and cuttable LED strip
- Smallest cuttable unit: 100 mm
- Lifetime (L70/B50): up to 30,000 h at Tc max.: 75°C
- Luminous flux: 2000 lm/m
- Color rendering index R_a : > 80
- Large range of color temperatures: from warm white to cool daylight
- Dimmable with suitable drivers, see also www.ledvance.com/dim

TECHNICAL DATA

Electrical data

Nominal wattage	70.00 W
Construction wattage	70.00 W
Nominal wattage per meter	16.0 W
Nominal voltage	24 V
Input voltage range	23...25 V
Type of current	DC
Nominal current	2917 mA

Photometrical data

Luminous efficacy	106 lm/W ¹⁾
Luminous flux	6790 lm
Luminous flux per meter	1695 lm ¹⁾
Color temperature	2700 K
Color rendering index Ra	> 80
Light color LED	Warm White
Light color (designation)	Warm White
Standard deviation of color matching	≤5 sdcn

¹⁾ Value based on first meter of the product


Light technical data

Beam angle	120 °
Rated beam angle (half peak value)	120.00 °

LED MODULE INFORMATION

Number of LEDs per meter	70
Number of LEDs per module	350
Number of LEDs per smallest unit	7

Dimensions & Weight



Length	5000.00 mm
Length – smallest unit	100 mm

Cable length	500.000
Width	8.00 mm
Height	1.50 mm
Prewired	Yes
Conductor cross section	0.5 mm ²
LED pitch	14.29 mm
Short pitch	No
Product weight	78.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+55 °C
Maximum temperature at tc test point	75 °C

Lifespan

Nominal lamp life time	30000 h
------------------------	---------

Capabilities

Dimmable	Yes ¹⁾
Lowest bending radius	30,0 mm
Self-adhesive	Yes

¹⁾ Dimmable with suitable drivers, see also www.ledvance.com/dim


Certificates & Standards












Approval marks – approval	CE / TUV
Protection class	III
Type of protection	IP00
Energy class of contained light source	F
Salt mist resistance acc. IEC 60068-2-52	No
UV resistance acc. IEC 60068-2-5	No













LOGISTICAL DATA













Temperature range at storage	-20...+80 °C
------------------------------	--------------


Accessories Optional

Product image	Product name	EAN
	LS AY -CSW/P2/50	4058075727434

Product image	Product name	EAN
	LS AY -CSD/P2	4058075727526
	LS AY -8/SMB	4058075727588
	LS AY -CP/P2/500	4058075727403
	LS AY -PF02/U/16X5/10/1	4058075278226
	LS AY -PM04/UW/23X15,5/10/1	4058075278400
	LS AY -PF04/U/17X7/12/1	4058075278288
	LS AY -PM02/R/18X15,5/10/1	4058075278349
	LS AY -PM03/E/19X19/10/2	4058075401716
	LS AY -PM05/U/17,5X14,5/10/1	4058075279278
	LS AY -PF01/UW/22X6/10/1	4058075278196
	LS AY -PM06/E/18X18/12/1	4058075279308
	LS AY -PM05/U/17,5X14,5/10/2	4058075401778

Product image	Product name	EAN
	LS AY -PF01/UW/22X6/10/2	4058075401532
	LS AY -PF02/U/16X5/10/2	4058075401563
	LS AY -PF03/UW/25X7/12/1	4058075278257
	LS AY -PM04/UW/23X15,5/10/2	4058075401747
	LS AY -PW01/U/26X8/14/1	4058075278103
	LS AY -PF04/U/17X7/12/2	4058075401624
	LS AY -PM02/R/18X15,5/10/2	4058075401686
	LS AY -PM01/UW/21,5X12/10/1	4058075278318
	LS AY -PM03/E/19X19/10/1	4058075278370
	LS AY -PW02/UW/39X26/14/1	4058075278134
	LS AY -PW03/U/26X26/14/2	4058075401501
	LS AY -PM06/E/18X18/12/2	4058075401808




Product image	Product name	EAN
	LS AY -PM01/UW/21,5X12/10/2	4058075401655
	LS AY -PW01/U/26X8/14/2	4058075401440
	LS AY -PW02/UW/39X26/14/2	4058075401471
	LS AY -PW03/U/26X26/14/1	4058075278165
	LS AY -PF03/UW/25X7/12/2	4058075401594
	DR-PFM -100/220-240/24/P	4058075239937
	DR-PFM -150/220-240/24/P	4058075239975
	DR-PFM -250/220-240/24/P	4058075240032
	DR DIM-PFM -250/220-240/24/P	4058075240155
	DR DIM-PFM -150/220-240/24/P	4058075240117
	DR DIM-PFM -100/220-240/24/P	4058075240070
	DR-VAL -120/220-240/24	4058075240131




Product image	Product name	EAN
	DR-VAL -150/220-240/24	4058075240179


EQUIPMENT / ACCESSORIES

– Connectors, profiles and covers for several mounting options available

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	LS V IP00
 Legal information	LS Insert LED STRIP V IP00
 Declarations of conformity	Declaration of Conformity LS V

Photometric and lighting design files	Document name
 IES file (IES)	LS V-2000-827-5
 LDT file (Eulumdat)	LS V-2000-827-5
 Light distribution curve type polar	LS V-2000-827-5

Tender texts	Document name
 Tender documents	LED STRIP V 2000 827 5-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075708037	Folding box 1	242 mm x 242 mm x 26 mm	426.00 g	1.52 dm ³
4058075708044	Shipping box 30	450 mm x 420 mm x 230 mm	6910.00 g	43.47 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.