

## PRODUCT DATASHEET NAV-T 150 W SUPER XT

VIALOX® NAV®-T SUPER XT | High-pressure sodium vapor lamps for open and enclosed luminaires



### Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires
- Alternative to sodium twin arc lamps

### Product benefits

- Very long lifetime
- Very high luminous efficacy
- Extended service time (lamp replacement cycle): 8 years (at approx. 11 h/day)
- Very good luminous flux maintenance throughout the life of the lamp
- Optimum energy efficiency on POWERTRONIC® PTo 3DIM ECGs



### Product features

- Lamp survival rate: 95 % after 28,000 h burning time
- Lamp maintenance factor:  $\geq 80$  % after 24,000 h burning time (according to DIN 13201)
- Dimmable on conventional control gears and electronic control gears

**TECHNICAL DATA**


**Electrical data**

Nominal wattage	150 W
Construction wattage	159.80 W
Nominal voltage	100 V
Ignition voltage	3.3 5.0 kVp <sup>1)</sup>
Nominal current	1.8 A
PFC capacitor at 50 Hz	20 µF

<sup>1)</sup> Minimum / Maximum

**Photometrical data**

Luminous flux	18000 lm
Luminous efficacy	113 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.98
Rated LLMF at 4,000 h	0.97
Rated LLMF at 6,000 h	0.96
Rated LLMF at 8,000 h	0.95
Rated LLMF at 12,000 h	0.94
Rated LLMF at 16,000 h	0.94
Rated LLMF at 20,000 h	0.94
UV protection	No



**Dimensions & Weight**

Overall length	211.00 mm
----------------	-----------

Light center length (LCL)	132,0 mm
Diameter	47.00 mm
Product weight	115.00 g

### Temperatures & operating conditions

Maximum permitted outer bulb temperature	310 °C
Maximum permitted base edge temperature	210 °C

### Lifespan

Lifespan	48000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000	0.99
Rated lamp survival factor at 6,000	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.99
Rated lamp survival factor at 20,000 h	0.99
Lifespan B10	34000 h
Lifespan B5	28000 h
Lifespan B50	48000 h

### Additional product data

Base (standard designation)	E40
Mercury content	21.6 mg
Design / version	Clear
Product remark	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable

### Capabilities

Dimmable	Yes <sup>1)</sup>
Burning position	Any
Enclosed luminaire required	No
Hot restart	No

<sup>1)</sup> In combination with POWERTRONIC PTo

### Certificates & Standards

Energy efficiency class	F
-------------------------	---

Energy consumption	160.00 kWh/1000h
--------------------	------------------




Country-specific categorizations

ILCOS	ST-150-H/E/SL-E40-47/210
Order reference	NAV-T 150WSUPER

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	HPS
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	E40
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	211.00 mm
Height	47.00 mm
Width	47.00 mm
Chromaticity coordinate x	0,535
Chromaticity coordinate y	0,420
Beam angle correspondence	SPHERE_360
EPREL ID	546599
Model number	AC34394

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	Certificates
	Certificates

## DOWNLOAD DATA



Declarations Of Conformity CE

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075803572	Sleeve 1	52 mm x 52 mm x 260 mm	148.00 g	0.70 dm <sup>3</sup>
4058075803701	Shipping box 12	216 mm x 166 mm x 272 mm	1807.00 g	9.75 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.