



Ledinaire Waterproof Tube Housing

WT050C 2xTLED L1500

- 220 to 240 V - 50 or 60 Hz - Safety class II - - - IP65 | Dust penetration-protected, jet-proof - IK08 | 5 J vandal-protected - White

The Ledinaire waterproof (WT050C) range contains a selection of empty, waterproof housings, that can cater for LED tubes of your choice. It comes with the high Philips quality levels at a competitive price. Ledinaire enables, simple and quick installation, with a choice of single and double tube installations.

Product data

General Information	
Angle	-
Accessory color	White
Value ladder	Value
Light Technical	
Color rendering index (CRI)	-
Luminaire light beam spread	-
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz

Mechanical and Housing	
Overall length	1,580 mm
Overall width	95 mm
Overall height	84 mm
Dimensions (Height x Width x Depth)	84 x 95 x 1580 mm
Material	Polycarbonate
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class II
Product Data	
Full product code	871016336605099
Order product name	WT050C 2xTLED L1500

Ledinaire Waterproof Tube Housing

Order code	911401807681
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	9
Material number (12NC)	911401807681
Full product name	WT050C 2xTLED L1500

EAN/UPC - Case	8710163366210
----------------	---------------



Dimensional drawing

