



PrimaVision Compact for CDM

HID-PV C 35 /I CDM 220-240V 50/60Hz NG

High-quality, compact and lightweight HID electronic gear for optimal and reliable performance of 20, 35, 50 and 70 W CDM lamps

Product data

General Information		Mechanical and Housing	
Number of Lamps	1 piece/unit	Housing	/I
Operating and Electrical		Approval and Application	
Input Voltage	220 to 240 V	Safety Standard	EN 61347-2-12
Line Frequency	50 to 60 Hz	Environmental Standard	ISO 14001
Input Frequency	50 to 60 Hz	Approval Marks	CE marking ENEC certificate
Earth Leakage Current (Max)	0.25 mA	Product Data	
Inrush Current Width	0.25 ms	Full product code	872790085973700
Inrush Current Peak (Max)	26 A	Order product name	HID-PV C 35 /I CDM 220-240V 50/60Hz NG
Number of Products on MCB (16A Type B) (Nom)	24	Order code	913700653166
Wiring		Numerator - Quantity Per Pack	1
Cable Length From Device to Lamp	2.0 m	Numerator - Packs per outer box	12
Connector Type	Insert	Material number (12NC)	913700653166
Temperature		Full product name	HID-PV C 35 /I CDM 220-240V 50/60Hz NG
Ambient temperature range	-20 °C to 50 °C	EAN/UPC - Case	8727900859737
T-Case Lifetime (Nom)	75 °C		
T-Case Maximum (Max)	75 °C		

PrimaVision Compact for CDM

Dimensional drawing

A2

Product	D1	C1	A1	A2	B1
HID-PV C 35 /I CDM 220-240V 50/60Hz NG	4.8 mm	34.5 mm	188.0 mm	170.0 mm	82.7 mm

