



Coreline tempo small gen2

BVP111 LED49-4S/730 OFA52

Coreline tempo small gen2, Floodlight, 31 W, 4263 lumen, 3000 K, CRI70, Asymmetrical, IP66

Coreline tempo small gen2 delivers on the Coreline promise of innovative, easy to use and high-quality floodlight. A limited range of options makes it easy to find the best lux-for-lux replacement for conventional technologies and direct replacement of 70W and 100W HID lamps. The CoreLine tempo small gen2 offers 2 lumen packages for different application areas as well as 2 high-performance asymmetrical and symmetrical optics. Installing this LED floodlight is made easy thanks to the U-shaped mounting bracket and the external quick 3-poles connector. It is an ideal flood lighting solution for outdoor environments such as industrial/commercial areas, parking lots, etc.

Product data

General Information		Light Technical	
Lamp family code	LED49 [LED module 4900 lm]	Upward light output ratio	0
Number of gear units	1 unit	Luminous Flux	4,263 lumen
Driver included	Yes	Standard tilt angle posttop	0°
Light source engine type	LED	Standard tilt angle side entry	0°
Product family code	BVP111 [Coreline tempo small gen2]	Correlated Color Temperature (Nom)	3000 K
Lighting Technology	LED	Luminous Efficacy (rated) (Nom)	136 lm/W
Value ladder	Performance	Color rendering index (CRI)	70
CE mark	Yes	Light source color	730 warm white
Warranty period	5 years	ENEC mark	ENEC mark
Flammability mark	For mounting on normally flammable surfaces	EU RoHS compliant	Yes

Coreline tempo small gen2

Optical cover type	Flat glass
Luminaire light beam spread	60° x 120°
Optic type outdoor	Asymmetrical

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	18 A
Inrush time	0.3 ms
Power Consumption	31 W
Power Factor (Fraction)	0.9
Connection	External connector
Cable	Cable 1.0 m with plug Wieland/Adels compatible 3-pole
Number of products on MCB of 16 A type B	30

Temperature

Ambient temperature range	-40 to +45 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Glass
Fixation material	Aluminum
Housing Color	Gray
Mounting device	Wall-mounting bracket
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	286.9 mm
Overall width	211.5 mm
Overall height	64 mm
Effective projected area	0.02 m²
Dimensions (Height x Width x Depth)	64 x 212 x 287 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
-------------------------	--

Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 8 kV common mode

Sustainability rating	-
Protection class IEC	Safety class I
Photobiological risk	Photobiological risk group 1 @200mm to EN62778

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.382, 0.379) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 75000 h	10 %
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 75000 h	L80
Lumen maintenance at median useful life* 100000 h	L80

Application Conditions

Performance ambient temperature Tq	25 °C
------------------------------------	-------

Product Data

Full product code	872016955681200
Order product name	BVP111 LED49-4S/730 OFA52
Order code	912300060468
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912300060468
Full product name	BVP111 LED49-4S/730 OFA52
EAN/UPC - Case	8720169556812
EAN/UPC - Product/Case	8720169556812

Coreline tempo small gen2

Dimensional drawing

