

Produktdetails

62764-83-WL-500

62764-83-WL-500 WD 180 flex multi sens. WL



Allgemeine Informationen

Typ	62764-83-WL-500
Bestellnummer	2CKA006200A0238
EAN	4011395292662
Beschreibung	62764-83-WL-500 WD 180 flex multi sens. WL

Langbeschreibung	<p>Movement detector sensor with with measurement of ambient light. For automatic switching of devices dependent on motion and brightness. Push switch function possible at all times. For detection down to the floor. For detection in stairwells. With 4 detection levels. In combination with dimmer insert flex: dimming function of lighting and selectable light value storage. With time-controlled basic illumination function. With time-controlled night anti-glare function. With enabling of pre-warning of switch-off for stairwell operation. Compatible with all free@home flex inserts. Remote operation via the Bluetooth and smartphone/tablet app. Multi-lens: suitable also for mounting heights of 2.20 m. Extension of the detection range by means of master/slave combination. Timer with Astro function. Automatic switchover from summer time to winter time (switch-off function). With continuous light/continuous Off function. With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Surveillance density: 54 sectors with 224 switching segments. Switch-off delay: approx. 10 sec - 30 min or short-time pulse 1 sec adjustable. For relay insert flex, 1gang, 64811 U. For e-contact insert flex, 1gang, 64814 U. For series relay insert flex, 2gang, 64821 U.</p>
------------------	---

Installation / Montage

Betriebs- und Montageanleitung	No document needed
--------------------------------	--------------------

Technische Daten

Datenblatt, technische Information	No document needed
Geeignet für	2CKA006800A3042 2CKA006800A3048 2CKA006800A3045 2CKA006500A0013 2CKA006800A3051
Unterstützte Bussysteme	free@home
Produktreihe	Busch-flexTronics® Busch-free@home®
Schalterdesign	63x63 future® linear Busch-axcent® Busch-axcent pur
Minimalste Umschaltzeit	einschalten 30 Sekunde(n)
Montageart	Flush Mounted
Werkstoff	Thermoplastischer Kunststoff
Ausführung	Bewegungssensor
RAL Nummer	RAL 9006 - weißaluminium
Farbe	alusilber
Chemische Batteriezusammensetzung	Lithium, nicht aufladbar
Batterieart	Knopfzelle
Batteriegewicht	0.07 g
Anwendungsbereich	Elektrische Last- und Lichtsteuerung

Umwelt

Umgebungstemperatur	-5...45 °C
Schutzart	IP20
RoHS Status	nach EU-Richtlinie 2015/863 22. Juli 2019 (RoHS 3)
RoHS Information	2CKA200000E7427
REACH Erklärung	2CKA309999E9999

Abmessungen

Breite des Produkts	63 mm
Höhe des Produkts	63 mm
Tiefe des Produkts	44 mm
Nettogewicht	34 g

Bestelldaten

Mindestbestellmenge	1 Stück
Menge Verpackungseinheit 1	Karton 1 Stück
Bruttogewicht Verpackungseinheit 1	0.071 kg
Zolltarifnummer	85389099
E-Nummer (Finnland)	2815706
Herkunftsland	Deutschland (DE)

Zertifikate und Deklarationen

Konformitätserklärung - CE	No declaration needed
----------------------------	-----------------------

Klassifizierungen

ETIM 8	EC000138 - Bewegungsmelder-Sensor
ETIM 9	EC000138 - Bewegungsmelder-Sensor
WEEE Kategorie	5. Geräte, bei denen keine der äußeren Abmessungen mehr als 50 cm beträgt (Kleingeräte)
WEEE B2C / B2B	B2C
CN8	8538 90 99
eClass	V11.0 : 27144008

Kategorien

Niederspannungsprodukte und Systeme → Haus- und Gebäudeautomation → free@home → Bedienen → Solo → Bewegungsmelder

