

Product Data Sheet

GWJ2103L100

JOINON range



The wall-mounted I-ON charging stations are the JOINON solutions for public and semi-public access, designed for charging electric vehicles and to withstand any wear including impacts, stress, vandalism and atmospheric agents. They are the first and only on the market guaranteed with a IP55 protection rating. The special design allows the units to be adapted into any urban context and parking configuration, with a targeted focus on the user experience of drivers. They are available with standard JoinOn graphics, which may be customised on request.

INPUT		- Socket/Connector Nr. (Type)		2 (Type 2 vandal-proof socket, with shutters)	
Terminal blocks	2 x (5 x 10 mm ²)	Charging activation	Remotely managed, via OCPP 1.6J		
Rated current	64 A	Human Interface	LED RGB and TFT Display		
Total power	44 Kilowatt	Connectivity	LAN		
OUTPUT		- MECHANICAL FACTS		-	
Rated voltage	400 V	Mounting and installation	Wall mount		
Current supplied (max)	32 A per socket	Colour	Grey, Headboard RAL 7011		
Power max.	22 kW per socket	Material	Steel sheet		
Thermal-magnetic protection	Currently not present	External treatments	Anti-corrosion and anti-graffiti		
Type of residual current protection	Currently not present	IP degree	IP55		
Power meter	YES (MID)	Mechanical resistance	IK10		
DC Leakage check	Currently not present	Operating temperature	-25 +50 °C		
(Auto)restart electrical protections	Currently not present	Customizations	Yes (front)		

DIMENSIONAL

TECHNICAL SYMBOLOGY

IP

IK

IP55

IK10

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 20/04/2023

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice