

SLI047101NW_PW

SLI047101NW_PW



See
more



Power **75 W**

Colour temperature **4000 K**

Beam angle **30 °**

Voltage **230 V**

Colour of light **Neutral white**

Degree of protection (IP) **IP40**

Technical data

| | |
|------------------------------|---|
| Code | SLI047101NW_PW |
| Power | 75 W |
| Nominal current | 335 mA |
| Voltage | 230 V |
| Energy consumption | 75 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.98 |
| Useful luminous flux* | 13500 lm (360°) |
| Luminous flux** | 12750 lm (360°) |
| Lamp efficacy | 180 lm/W |
| Colour temperature | 4000 K |
| Colour of light | Neutral white |
| Beam angle | 30 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | DALI |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum/PC |
| Degree of protection (IP) | IP40 |
| Colour | White |
| Dimension (AxBxC) | 1438x65x40 mm |
| For use | Inside |
| Assembly method | On the ceiling, Suspended |
| Application | INTERNAL |
| Made in | PRC |
| Other | Max ilość opraw na zabezpieczenie nadprądowe: , |

Related documents



 User manual



 Declaration of Conformity



 Photometric file

