

# TRAGO mini GU10

WQJP06252

Smart LED luminaire TRAGO mini GU10 and remote commissioning and control via the app on your mobile device. Narrow beam angle 50° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



Power	<b>5 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>480 lm (90°)</b>	Colour temperature	<b>2700-6500 K</b>
Colour of light	<b>CCT/RGB</b>	Beam angle	<b>50 °</b>
Degree of protection (IP)	<b>IP20</b>		

## Technical data


---

Code	WQJP06252
Power	5 W
Nominal current	45 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	5 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	SMART
Power factor	0,5
Useful luminous flux*	480 lm (90°)
Luminous flux**	480 lm (360°)
Lamp efficacy	96 lm/W
Luminous intensity	480 cd
Colour temperature	2700-6500 K
Colour of light	CCT/RGB
Beam angle	50 °
RA	80
Light source included	+
Uniformity of color SDCM max	3
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	50x175x145 mm
For use	Inside
Assembly method	on track
Application	INT
Made in	PL
Other	RGBW ,

## Related documents

---



 Declaration of Conformity

---