



# MASTERColour CDM-TC Elite

## MASTERC CDM-TC Elite 50W/930 G8.5 1CT/12

Compact, single-ended, very high-efficiency, long-life ceramic metal-halide discharge lamp producing crisp white sparkling light with high color rendering

### Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G8.5 [G8.5]		91
Operating Position	UNIVERSAL [Any or Universal (U)]	Operating and Electrical	
Flux measurement reference	Sphere	Power Consumption	50.2 W
		Voltage (Nom)	90 V
		Voltage (Nom)	90 V
Light Technical		Controls and Dimming	
Color Code	930 [CCT of 3000K]	Dimmable	No
Luminous Flux	5,400 lumen	Mechanical and Housing	
Color Designation	Warm White (WW)	Bulb Finish	Clear
Chromaticity Coordinate X (Nom)	0.434	Bulb Shape	T14 [T 14 mm]
Chromaticity Coordinate Y (Nom)	0.398		
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	108 lm/W		

# MASTERC colour CDM-TC Elite

## Approval and Application

Mercury (Hg) Content (Max)	6.6 mg
Mercury (Hg) Content (Nom)	6.6 mg
Energy Consumption kWh/1000 h	51 kWh
EPREL Registration Number	473,270

## Product Data

Full product code	872790093062700
Order product name	MASTERC CDM-TC Elite 50W/930 G8.5 1CT/12


Order code	928191805131
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	928191805131
Full product name	MASTERC CDM-TC Elite 50W/930 G8.5 1CT/12
EAN/UPC - Case	8727900930634

## Dimensional drawing

. D .

Product	D (max)	O	L (min)	L (max)	L	C (max)
MASTERC CDM-TC Elite 50W/930 G8.5 1CT/12	15 mm	6 mm	51 mm	53 mm	52 mm	85 mm


## Photometric data



Spectral Power Distribution Colour - MASTERC CDM-TC Elite 50W/930 G8.5 1CT/12

# MASTERC colour CDM-TC Elite

## Lifetime



Lumen Maintenance Diagram - MASTERC CDM-TC Elite 50W/930 G8.5 1CT/12

Life Expectancy Diagram - MASTERC CDM-TC Elite 50W/930 G8.5 1CT/12

