



MASTER PL-S 2 Pin

MASTER PL-S 11W/830/2P 1CT/5X10BOX

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base

Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Color rendering index (CRI)	
Cap-Base	G23 [G23]		82
Flux measurement reference	Sphere		
Light Technical		Operating and Electrical	
Color Code	830 [CCT of 3000K]	Power Consumption	11.9 W
Luminous Flux	900 lumen	Lamp Current (Nom)	0.155 A
Color Designation	Warm White (WW)		
Chromaticity Coordinate X (Nom)	0.44	Controls and Dimming	
Chromaticity Coordinate Y (Nom)	0.403	Dimmable	No
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	77 lm/W	Approval and Application	
		Mercury (Hg) Content (Max)	1.4 mg
		Mercury (Hg) Content (Nom)	1.4 mg

MASTER PL-S 2 Pin

Energy Consumption kWh/1000 h	12 kWh
EPREL Registration Number	423,597
Product Data	
Full product code	871150026106970
Order product name	MASTER PL-S 11W/830/2P 1CT/5X10BOX
Order code	927936483011


Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material number (12NC)	927936483011
Full product name	MASTER PL-S 11W/830/2P 1CT/5X10BOX
EAN/UPC - Case	8711500261083

Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-S 11W/830/2P 1CT/ 5X10BOX	28 mm	13 mm	198 mm	214 mm	235.8 mm

Photometric data



Spectral Power Distribution Colour - MASTER PL-S 11W/830/2P 1CT/5X10BOX

Lifetime



Life Expectancy Diagram - MASTER PL-S 11W/830/2P 1CT/5X10BOX

Life Expectancy Diagram - MASTER PL-S 11W/830/2P 1CT/5X10BOX

MASTER PL-S 2 Pin

Lifetime



Lumen Maintenance Diagram - MASTER PL-S 11W/830/2P 1CT/5X10BOX

