



PrimaVision for SDW-TG

HID-PV 100 /S SDW-TG 220-240V 50/60Hz


Robust, lightweight and one-piece HID electronic gear for SDW-TG lamps (mini White SON) Lightweight, one-piece electronic gear for 50 and 100 W SDW-TG lamps (mini White SON)

Product data

General Information		T-Case Maximum (Max)	
Number of Lamps	1 piece/unit		85 °C
Operating and Electrical		Mechanical and Housing	
Input Voltage	220 to 240 V	Housing	/S
Line Frequency	50 to 60 Hz	Approval and Application	
Input Frequency	50 to 60 Hz	Approval Marks	CE marking ENEC certificate CB Certificate
Inrush Current Width	0.50 ms	Product Data	
Inrush Current Peak (Max)	33 A	Full product code	872790088754900
Number of Products on MCB (16A Type B) (Nom)	14	Order product name	HID-PV 100 /S SDW-TG 220-240V 50/60Hz
Wiring		Order code	913700656566
Cable Length From Device to Lamp	2 m	Numerator - Quantity Per Pack	1
Connector Type	Insert	Numerator - Packs per outer box	10
Temperature		Material number (12NC)	913700656566
Ambient temperature range	-20 °C to 60 °C	Full product name	HID-PV 100 /S SDW-TG 220-240V 50/60Hz
T-Case Lifetime (Nom)	75 °C	EAN/UPC - Case	8727900887549

PrimaVision for SDW-TG

Dimensional drawing



Product	D1	C1	A1	A2	B1	B2
HID-PV 100 /S SDW-TG 220-240V 50/60Hz	4.5 mm	37.0 mm	150.0 mm	133.6 mm	90.0 mm	70.0 mm

