

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** PHILIPS

**Supplier's address:** Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

**Model identifier:** 8711500260574

## Type of light source:

|   |       |                                 |      |
|---|-------|---------------------------------|------|
| Lighting technology used:                           | CFLni | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | G23   |                                 |      |
| Mains or non-mains:                                 | NMLS  | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No    | Envelope:                       | -    |
| High luminance light source:                        | No    |                                 |      |
| Anti-glare shield:                                  | No    | Dimmable:                       | No   |

## Product parameters

| Parameter  | Value                | Parameter  | Value                              |
|--|----------------------|--|------------------------------------|
| <b>General product parameters:</b>   |                      |  |                                    |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 8                    | Energy efficiency class  | G                                  |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 400 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700                              |
| On-mode power ( $P_{on}$ ), expressed in W   | 7,2                  | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                               |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                    | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 82                                 |
| Outer dimensions without   | Height               | 135  | Spectral power distribution in the |
|  | Width                | 28   |                                    |
|  | Depth                | 28   |                                    |
|  |                      |  | See image in last page             |

|   |   |                                      |                |
|---|---|--------------------------------------|----------------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) |   | range 250 nm to 800 nm, at full-load |                |
| Claim of equivalent power <sup>(a)</sup>  | - | If yes, equivalent power (W)         | -              |
|   |   | Chromaticity coordinates (x and y)   | 0,463<br>0,420 |

(a) '-': not applicable;

(b) '-': not applicable;

